

PORTABLE EMERGENCY EYEWASHES

Self-contained emergency eyewash units, also known as portable eyewash units, contain a large volume reservoir of flushing fluid within to provide a continuous 15-minute flow. They are ideal for locations without access to potable water or for locations where eyewash access needs to be moved at a moments notice.

Haws® portable eyewash units meet all ANSI requirements for flow rates, stream heights, and pressure for the full flushing duration and are CSA certified to ANSI/ISEA Z358.1-2014.

7501



GRAVITY-FED EYEWASHES

Model 7501

Portable 9-gallon (34.1 L) eyewash, polyethylene tank with yellow pull-down activation arm. The unit supplies a continuous flow of water for a full 15 minutes at .4 GPM (1.5 LPM).

7501T



Model 7501T

Portable 9-gallon (34.1 L) tempered portable eyewash with a heated, insulated blanket to provide ANSI compliant tempered, potable water in ambient operating temperatures from -20°F (-29°C) to 100°F (38°C). 120V electrical requirement with supplied 8' GFCI power cord. Additional HazLoc and 240V options available.

7501BL



Model 7501BL

Heated, insulated blanket to provide ANSI compliant tempered, potable water in ambient operating temperatures from -20°F (-29°C) to 100°F (38°C). The self-contained heating blanket easily installs on to existing model 7501 units and the electrical system uses NEMA 3R rated components. 120V electrical requirement with supplied 8' GFCI power cord. Eyewash and heating blanket offered as a package or individually. Additional HazLoc and 240V options available.

7500EB



Model 7500EB

Portable 16-gallon (60.6 L) heated eyewash is freeze-resistant and fully functional to -30°F (-34.4°C). Water is tempered between 65° and 75°F (18.3 and 23.9°C) using a 1000 Watt, 120 VAC submersible thermostatically-controlled heater element. The unit supplies a continuous flow of water for a full 15 minutes at .4 GPM (1.5 LPM). Available without heating blanket, Model 7500.

TEMPERED



AIR-PRESSURIZED EYEWASHES

7601.15



Model 7601.15

Portable 15-gallon (57 L) eyewash with stainless steel ASME rated tank with an air pressure gauge, pressure relief valve, tire-type air fill valve. The unit provides approximately 10 usable gallons (37.9 liters) of water for effective rinsing. Optional transport cart, Model 9008, and optional drench hose, Model 8901B, available.

Model 7601.37

Portable eyewash and body spray. Features a 37-gallon (140 L) capacity ASME rated stainless steel tank with an air pressure gauge, pressure relief valve, tire-type air fill valve and a 6-foot (182.9 cm) drench hose.

Model 7603

Portable 15-gallon (57 L) eyewash with stainless steel tank with an air pressure gauge, pressure relief valve, tire-type air fill valve. The unit provides approximately 10 usable gallons (37.9 liters) of water for effective rinsing. Optional transport cart, Model 9008, and optional drench hose, Model 8901B, available.

7601.37



Model 7603T

Portable 15-gallon eyewash that uses a heated, insulated blanket to provide ANSI-compliant tempered, potable water in ambient operating temperatures from -20°F (-29°C) to 100°F (38°C). The unit provides approximately 10 usable gallons (37.9 liters) of water for effective rinsing. 120V electrical requirement with supplied 8' GFCI power cord. Additional HazLoc and 240V options available.

Model 7603BL

Heated, insulated blanket to provide ANSI compliant tempered, potable water in ambient operating temperatures from -20°F (-29°C) to 100°F (38°C). The self-contained heating blanket easily installs on to existing model 7603 units and the electrical system uses NEMA 3R rated components. 120V electrical requirement with supplied 8' GFCI power cord. Eyewash and heating blanket offered as a package or individually. Additional HazLoc and 240V options available.

7603



7603T



7603BL

